



CITY OF LODI

PUBLIC WORKS DEPARTMENT

Sign Post Installation

Notes:

1. Concrete For Post Installation May Be Class C Concrete.
2. Posts shall be new 2"x 2" 14 gauge galv. tube set plumb.
3. When Sign Square Footage Is 7.5 Square Feet or More Post Shall Be 2" x 2" 12 Gauge galv. Tube.
4. Posts Shall Be Select Punch Both Ends, 12" from bottom end and no greater than sign height at top end, on four Sides.
5. Street Name And Traffic Signs Per Std Plan 142, a min. vertical clearance of 9'-6" at locations with street name signs only.
6. R10's (one way signs) To Be Located 1.5' from bottom of sign When placed in the median.
7. A Powder Coat (Downtown Green) Is Required For Downtown Locations. Form And Edge 12" x 12" Concrete Apron in dirt locations.
8. 4" Thick In Dirt Locations, When Required By Engineer.
9. Min. vertical clearance of 6'-6" at locations with multiple signs. (not including street name signs.)

Page 2 of 2

Dr. GWC	No. 1	Date 2/04	Revision ADDITION OF SECOND PAGE	Appr.	Approved By: <i>F. Wally Sandell</i>	STD PLAN
Ch. WS					<i>F. Wally Sandell</i> 2/12/04	119
Date					F. Wally Sandell City Engineer R.C.E. 39895	